

Fentrim F[®]

high-performance adhesive flashing



Choose Fentrim F for primer-free adhesion in above-grade masonry connections, window flashing, and other critical building envelope details.

SIGA Fentrim F is a fleece-backed, semi-permeable acrylic flashing tape. The robust, polyolefin (PO) carrier resists jobsite abrasions while remaining formable and pliable, even in below freezing temperatures. Fentrim F offers superior adhesion to cured concrete, metal, and wood.

CHARACTERISTICS

AVAILABLE WIDTHS	4", 6", 9"
ROLL LENGTH	82 ft
THICKNESS	26 MILS
MAX UV EXPOSURE	3 MONTHS
WATER VAPOR TRANSMISSION	1.7 US PERMS

- ✓ high adhesive strength at high and low temperatures
- ✓ no primer required for masonry
- ✓ robust, fleece-backed carrier material



INSTALLATION INSTRUCTIONS / wall to foundation



- Clean substrate of any loose debris



- Pre-fold Fentrim F along split backing and dog-ear corner to start taping



- Apply to foundation, minimum 2"
- Remove lower backing strip and press on



- Remove upper backing strip, while maintaining full contact with substrate



- Fold tape up and onto wood wall
- Press on firmly



- How it should look

All SIGA products are backed by a 10-Year Limited Warranty. Refer to siga.swiss for complete details.

We want you to maximize SIGA's performance potential on your project. Contact one of our Application Advisors for support, from architectural detail review to jobsite training for installers.