

# Fentrim F<sup>®</sup>

## HIGH-PERFORMANCE ADHESIVE FLASHING



**Use Fentrim for durable WINDOW FLASHING, thru-wall flashing, and above-grade connections to masonry. WITHOUT LIQUID SEALANT. WITHOUT PRIMER.**

Fentrim F is a fleece-backed, semi-permeable acrylic flashing tape. The robust, polyolefin (PO) carrier resists jobsite abrasions while remaining formable and pliable, even in below freezing temperatures. Extremely high bond strength to cured concrete, metal, and wood.

### CHARACTERISTICS

AVAILABLE WIDTHS	4", 6", 9", 12"
ROLL LENGTH	82 FT
THICKNESS	26 MILS
WATER VAPOR TRANSMISSION	1.7 PERMS
UV STABILITY	3 MONTHS

- ✓ masonry-compatible without a primer
- ✓ sticks tenaciously in cold temperatures
- ✓ siliconized, split release liner saves time



# INSTALLATION INSTRUCTIONS



- Fold along the split backing.
- Seal to the inside corner and fold down onto the wall face.



- Remove backing strips and press on firmly.



- Seal all four corners and the perimeter of the rough opening.
- Install the window according to manufacturer's instruction.



- Counterflash the head and jambs with Fentrim.
- Integrate additional metal flashings or trim components as required.

All SIGA products are backed by a 10 year limited warranty. Reference [www.sigacover.com](http://www.sigacover.com) for complete details. We want you to maximize the performance potential of Fentrim F on your project. Contact one of our Application Advisors for assistance, from architectural details to jobsite training.